



Product Data

Activ Scooter 10W-30 4-AT

Continuous Protection

Description

In busy riding, scooter engines can run up to 15 degrees hotter than motorcycles, which can lead to higher wear and tear.

New Castrol Activ Scooter 4-AT with Actibond molecules clings to the engine to provide 3X protection: through start-up, while the engine is running, and when the engine is off

Application

Castrol Activ Scooter 10W-30 4-AT is suitable for all 4-stroke scooters of all manufacturers where API SL (and below) and/or JASO MB specifications are recommended.

Advantages

New Castrol Activ Scooter 4-AT delivers 3X protection*.

Castrol Activ Scooter 4-AT contains Actibond™ molecules that cling firmly to the engine parts.

Castrol Activ Scooter 4-AT:

- Provides 50% better** wear protection
- Fights deposits and provides outstanding engine cleanliness during running
- Provides excellent corrosion protection, even when the engine is off

*Protection in 3 stages of the ride: through engine start-up, running, and while the engine is off.

**vs reference API SL oil in Sequence IVA test

Typical Characteristics

Name	Method	Units	Castrol Activ Scooter 10W-30 4-AT
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic 100C	ASTM D445	mm²/s	11
Viscosity, Kinematic 40C	ASTM D445	mm²/s	73
Viscosity Index	ASTM D2270	None	135
Pour Point	ASTM D97	°C	-33

Product Performance Claims

API SL
JASO MB

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Activ Scooter 10W-30 4-AT
23 Dec 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com