



Product Data

Castrol GTX CNG 20W-50

For CNG Dual Fuel Vehicles

Description

Castrol GTX is one of the world's most trusted engine oils.

High performance Castrol GTX CNG is a multi-protection formula designed to provide superior protection for engines running on petrol and CNG fuel.

Dual fuel engines need extra protection at high temperatures.

Castrol GTX CNG contains "Radical Busters" that provide oxidation protection at high temperatures for CNG application and special anti-wear agents that provide superior wear protection when running on petrol.

Help extend the life of your engine with Castrol GTX.

Application

Castrol GTX CNG 20W-50 is suitable for use in automotive gasoline, CNG and diesel engines where the manufacturer recommends an API SG/CD or earlier specification 20W-50 lubricant.

Advantages

Castrol GTX CNG 20W-50:

- Provides oxidation protection at high operating temperatures
- Provides high and low temperature wear protection
- Engineered to protect against sludge build up
- Keeps engines cool and clean

Typical Characteristics

Name	Method	Units	Castrol GTX CNG 20W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.884
Viscosity, Kinematic 100C	ASTM D445	mm²/s	17.4
Viscosity, CCS -15C (20W)	ASTM D5293	mPa.s (cP)	6979
Viscosity, Kinematic 40C	ASTM D445	mm²/s	149
Viscosity Index	ASTM D2270	None	128
Pour Point	ASTM D97	°C	-27
Flash Point, PMCC	ASTM D93	°C	215
Ash, Sulphated	ASTM D874	% w t	0.7

Product Performance Claims

API SG/CD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX CNG 20W-50

21 Dec 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com